

Mobile Fencing & Security

Combi-Wood M824

Specifications

Dimensions Height (mm)	2000
Dimensions Width (mm)	2160
Package quantity	28
Weight (Kg)	29.5

Disclaimer: There are no rights to be derived from the technical specification. You should always consider up to 10% tolerance deviations. Heras herewith complies with NEN-EN 10305-3 © Heras.



Wooden temporary fence for a natural appearance

Balance between atmosphere and privacy

Thanks to the combination of wood and steel, the Combi-Wood fence offers a good balance between privacy and appearance. The lower section consists of a robust wooden panel, whilst the upper section is made of steel mesh. This obscures the view of equipment and work activities whilst maintaining a natural appearance.

- Appealing appearance thanks to the use of wood
- Ideal for lower-risk sites
- More sustainable fencing with a positive social impact

Practical design for low-risk construction sites

The upper section of the Combi-Wood temporary fence consists of a steel mesh with a wider mesh size of 100 mm. This open structure makes it easier to place a foot in the mesh and climb over the fence. This is precisely why this type of temporary fencing is suitable for sites where safety risks are more limited.

A temporary fence with a social impact

The wooden panels are manufactured by people reintegrating into the labour market. In this way, this fence not only contributes to the neat and efficient screening of your site, but also to social impact. This makes this temporary fencing an excellent choice for projects where appearance and social responsibility are just as important as functionality. Would you like to know more? Please contact us.