

Mobile Fencing & Security

42/42 High Security Coupler

Specifications

Dimensions Height (mm)	55
Dimensions Width (mm)	130
Dimensions Depth (mm)	
Package quantity	25
Weight (Kg)	0.48

Disclaimer: There are no rights to be derived from the technical specification. You should always consider up to 10% tolerance deviations. Heras herewith complies with NEN-EN 10305-3 © Heras.



Secure your fencing with the strongest clamp in our range

Keep unauthorised visitors out

The High Security fence clip prevents unauthorised individuals from opening or moving your fencing. It features a unique nut protection with a raised collar, making it impossible to loosen with standard tools. Only the special Heras Mobile Key, supplied when purchasing High Security Couplers, allows you to lock or unlock the connection. A variant is also available for semi-permanent setups, allowing fences to be attached directly to fixed posts.

- Can only be opened with the Heras Mobile High Security Key
- Available for both temporary and semi-permanent installation
- Reduces the need for on-site supervision

Smart to use, strong on security

To install, first place the fence in its footing. Then use the High Security Coupler to connect the fences. Loosen the nut, rotate the shields 90 degrees apart, position them around the fence tubes, and return them to their original position. For tightening, we recommend using a powered ratchet in combination with the special key. For semi-permanent situations, there is a variant with a shield designed for 60 mm diameter posts (instead of the standard 42 mm), ensuring that "fixed" really means fixed. Want more information about our High Security Couplers? Don't hesitate to contact us.