

# Mobile Fencing & Security

## 42/42 Security Coupler

### Specifications

Dimensions Height (mm)	55
Dimensions Width (mm)	130
Dimensions Depth (mm)	
Package quantity	25
Weight (Kg)	0.44

Disclaimer: There are no rights to be derived from the technical specification. You should always consider up to 10% tolerance deviations. Heras herewith complies with NEN-EN 10305-3 © Heras.



## The basic coupler for quick connections

### The basic solution for every fence line

With the standard fence coupler, you can easily connect temporary fence panels. The coupler is tightened from the inside of the site using a 19 mm spanner. Heras Mobile offers couplers for every situation, from basic installation to secure and semi-permanent applications. Properly connected fencing ensures a safe and reliable perimeter for your construction site.

- Functional and quick to install
- Fits round tubes of 42 mm diameter
- Simple and effective

### Straightforward installation and smart variants

First place the fence panels into their footings. Then loosen the nut, rotate the shields 90°, position them between the tubes, and rotate back. Finally, tighten the nut – preferably with an impact wrench for extra firmness. In addition to this standard coupler, High Security Couplers are available that can only be opened with a special key. For semi-permanent setups, couplers are also available with one side suitable for 60 mm posts. This ensures your fencing structure is securely fixed. Want to know more about installing fence couplers? Get in touch with us.