

Mobile Fencing & Security

Security coupler basic

Specifications

Dimensions Height (mm)	55
Dimensions Width (mm)	130
Dimensions Depth (mm)	
Package quantity	25
Weight (Kg)	0.28

Disclaimer: There are no rights to be derived from the technical specification. You should always consider up to 10% tolerance deviations. Heras herewith complies with NEN-EN 10305-3 © Heras.



The basic clip for easy locking temporary fences.

The basic solution for every fence line

The basic clip is a simple yet effective solution for connecting temporary fences. Each clamp is tightened from the inside of the site. Heras Mobile offers couplers for all scenarios from quick installation to secure or semi-permanent applications. Properly connected fences ensure a safe and clearly marked construction site boundary.

- Functional and easy to install
- Fits round tubes with a 42 mm diameter
- Straightforward and reliable

Clear installation and smart variants

Start by placing the fence panels into their footings. Then loosen the nut, rotate the plates 90°, insert them between the tubes and rotate them back. Finally, tighten the clamp securely, ideally using an impact wrench for added stability. In addition to this basic version, Heras also offers High Security Couplers that can only be opened with a special key. For semi-permanent setups, there are couplers with one side suitable for 60 mm posts, ensuring a truly secure fence construction. Want to know more about installing fence couplers? Contact us for more information.