

42/60 High Security Coupler

Specifications

| | |
|------------------------|------|
| Dimensions Height (mm) | 55 |
| Dimensions Width (mm) | 146 |
| Dimensions Depth (mm) | |
| Package quantity | 25 |
| Weight (Kg) | 0.54 |

Disclaimer: There are no rights to be derived from the technical specification. You should always consider up to 10% tolerance deviations. Heras herewith complies with NEN-EN 10305-3 © Heras.



Secure your fencing with the High Security Coupler in our range

Keep unauthorised visitors out

The 42/60 High Security Coupler prevents unauthorised access to your fencing system. Specifically developed for semi-permanent installations, this coupler features a unique nut protection with a raised collar, making it impossible to loosen with standard tools. The connection can only be opened or secured using the dedicated Heras High Security Key, available with the purchase of High Security Couplers.

- Can only be opened with the Heras High Security Key
- Designed for semi-permanent installations
- Reduces the need for daily site inspections

Smart to use, strong on security

First, the posts are driven into the ground. Then, the fence panels are attached between the posts using the couplers. Loosen the nut and rotate the shields apart. Turn the shields 90 degrees so one half fits between the fence and the post, then rotate back. Finally, tighten the coupler using the special key. For best results, use the key with a powered ratchet. Want more information about our High Security Couplers? Please don't hesitate to contact us.