

Mobile Fencing & Security

42/60 High Security coupler + Hinge ring

Specifications

Dimensions Height (mm)	55
Dimensions Width (mm)	150
Dimensions Depth (mm)	
Package quantity	15
Weight (Kg)	0.91

Disclaimer: There are no rights to be derived from the technical specification. You should always consider up to 10% tolerance deviations. Heras herewith complies with NEN-EN 10305-3 © Heras.



Create a gate quickly and safely with temporary fences

Easily create a gate in your fence line

Do you want your temporary fences to function as a swing gate? You can do this with our High Security solution including a hinge ring. In this solution, the High Security temporary fence coupler and the hinge ring are welded together. You only need to fix the coupler to the vertical tube of a temporary fence with a High Security key or standard nut. This allows the fence to move freely and function as an access gate.

- Simply solution to create a gate
- Easy to assemble
- Quick access to a site

Suitable for all temporary fences

The diameter of the hinge ring is 42 mm. You can therefore use this gate solution with all types of Heras temporary fences. However, the coupler including the hinge ring cannot be used for semi-permanent installations. The posts used for this purpose have a diameter of 60 mm, so the hinge ring does not fit around them. You can only create a swing gate with this solution when mounting temporary fences on our concrete or recycled footings.