

Mobile Fencing & Security

Anti-Lift system

Specifications

Dimensions Height (mm)	290
Dimensions Width (mm)	155
Dimensions Depth (mm)	
Package quantity	50
Weight (Kg)	0.5

Disclaimer: There are no rights to be derived from the technical specification. You should always consider up to 10% tolerance deviations. Heras herewith complies with NEN-EN 10305-3 © Heras.



Anti-Lift system makes it impossible to lift the fence

Prevent unwanted openings in your fence line

This anti-lift system ensures that temporary fences cannot be lifted out of a solid concrete block. The hook passes through the block and is then attached to the fence using a High Security clamp. This creates an additional connection that keeps the fence securely in place. The system is universally applicable, easy to install, and contributes to a safe and professional-looking site perimeter. If the footing does not have an extra "hole", a variant is available that can be placed sideways. The construction is simple, effective and has a long service life.

- Prevents fences from being lifted out
- Suitable for blocks with pre-drilled holes
- Compatible with temporary and semi-permanent setups

More security with minimal effort

Without an anti-lift system, fences can be tilted out of their footing. It is creating a weak spot in your site security. This system effectively prevents that risk. In combination with a High Security clamp, which can only be opened with a special key, unauthorised removal is nearly impossible. When mounted on the inside of the site and used in combination with Anti-Climb fences, you create a highly secure boundary that strongly deters intruders.